


BCB DUAL



Typical characteristics

Property	Rif.	Units	Range												
Basis Weight	ISO 536	g/m ²	+/-3%	85	120										
Moisture Index	ISO 287	%	+/-1%	7,5	7,5										
SCT, CD	ISO 9895	kN/m	-	1,50	2,2										
CMT 30, MD	ISO 7263	N	-	115	195										
Burst strength	ISO 2759	kPa	-	200	280										
Cobb-60 max	ISO 535	g/m2	-	35	35										

Guaranteed characteristics

Property	Rif.	Units													
SCT, CD	ISO 9895	kN/m	-	1,40	2,00										
CMT 30, MD	ISO 7263	N	-	105	170										
Burst strength	ISO 2759	kPa	-	170	240										

Mill : Verzuolo

CEPI code **52** **100 % RECYCLED**

End uses **high performance double purpose sized paper**

On demand available grammages out of TDS, with agreement on minimum lot, production optimization and tolerances

Certifications : available in FSC® or PEFC™ version



nov-20

Values referred to each quality are to be considered as reference data and could change without notice. Each value is subject to trade tolerances.

Sample collection following the EN-ISO 186 norm

Sample analysis following the EN-ISO 187 norm conditions: 23 °C +/- 1°C, 50%+/-2% R.H.